

**RESPONSE**

**IN THE CLAIMS:**

What is claimed is

1. (Currently Amended) A ~~method~~ computer program product for managing AV/C descriptor data, comprising ~~in combination instructions, which, when executed:~~  
compiling compile a plurality of containers containing AV/C descriptor data;  
registering register one or more fields within each said container; ~~and~~  
arranging arrange said containers into a logical hierarchy; ~~and~~;  
present the hierarchy to a device requesting data.
2. (Currently Amended) The ~~method~~ computer program product of claim 1, further comprising:  
instructions for associating addresses with each of said fields sequentially enumerated within each of said containers.
3. (Currently Amended) The ~~method~~ computer program product of claim 2, further comprising instructions for mapping said fields to a prescribed field list.
4. (Currently Amended) The ~~method~~ computer program product of claim 3, further comprising instructions for:  
accessing any field within any container independently of any other container;  
and  
reading data from any field within any container without affecting the access to any other container.

5. (Currently Amended) The ~~method computer program product~~ of claim 4, wherein said plurality of containers comprise in combination an AV/C general object list descriptor.

6-10. (Cancelled)

11. (Currently Amended) A ~~method computer program product~~ for compiling an AV/C descriptor readable buffer from one or more data containers, comprising ~~instructions, which, when executed~~ combination:

~~identifying~~ identify a top level data container containing AV/C descriptor data;  
~~initializing~~ initialize compilation attributes;  
sequentially reading the container data; and  
~~copying~~ copy said read data into a readable buffer.

12. (Currently Amended) The method of claim 11 wherein said ~~initializing activity~~ compilation attributes comprises in combination:

establishing a read buffer in a memory space and setting the read buffer offset to zero;  
establishing a received address request as a starting address;  
establishing a received read length request as a length sought.

13. (Currently Amended) The method of claim 12 wherein the sequentially reading container data activity includes ~~recursively~~ searching for responsive data, said ~~recursive~~ search initialized with said initialized attributes.